

Speedy 400

Laser engraving system

Mechanics

Working area	1016 x 610 mm (40 x 24 inch)
Loading area standard	1096 x 698 mm (43 x 27.4 inch)
Max. height of work piece	305 mm (12 inch) with 1.5 inch, 2.0 inch lens 292,5 mm (11.5 inch) with 2.0 inch clearance lens, 2.5 inch lens 255 mm (10 inch) with 4.0 inch lens 241,3 mm (9,5 inch) with 4.0 inch clearance lens
Working table	Multifunctional table concept, Rulers in mm or inches Electronic, programmable Z-axis with servo motor
Max. processing speed	4.32 m/s (170 ips)
Acceleration	50 m/s ² (1969 ips ²)
Motors	Brushless DC servo motors
Encoder	Incremental measuring system
Optical elements	Telescope, mirrors, lens
Lens	1.5 inch, 2.0 inch, 2.0 inch clearance, 2.5 inch, 4.0 inch, 4.0 inch clearance
Accuracy	+/- 0.015 mm (0.0006 inch), over the whole working area
Addressable accuracy	5 µm (0.0002 inch)
Accuracy to size of parts	According to material and process
Maximum material load	Static: up to 100kg (220 lbs), Dynamic: up to 30 kg (66 lbs) load over the whole working area
Interface	Ethernet, optional Wifi

Features standard

Lens	2.0 inch
InPack Technology™	Protects working head and all moving parts from dust
Exhaust	Surface exhaust via rear of the engraving cabinet, table exhaust with vacuum and cutting tables
Software	Ruby®
Operating console	Touch panel, keypad, safety-switch, system turnkey
Table	Aluminum cutting grid table
Laser Pointer	655nm, <0,99mWcw
Autofocus	Sonar Technology™
Work area light	LED
Additional standard features	Ergonomic access to working area, OptiMotion™, coaxial air assist incl. integrated pump, harsh environment protection kit, laser pointer, integrated partial coverable extraction slits, two Z-home positions, air-assist nozzles (Ø3 mm and Ø7 mm), lockable casters

Options

Vision Design&Position	Design and Position job in live view of work area on Ruby screen.
Temperature sensor	Should the temperature inside the engraving compartment exceed a critical value, the system will signal this to the operator by a warning sound. The operator then can take action immediately.
Gas-Kit light	Control of compressed air (free of mechanical dust, water and oil) max. flow rate 150 l/min (40 gpm) with max. 10 bar (145 psi);
Water cooling	CO ₂ laser sources with 60 W, 80 W or 120 W, external cooler needed
Screw feet	Additional to the rolls, for a good standing on the ground
Industrial interface	Start / Stop / ... signals to control the operation from extern

Accessories

Vision Print&Cut	Registration marks detection and compensation system Max. working area without camera: 1016 x 610 mm (40 x 24 inch) Max. working area with camera: 1004 x 610 mm (39.5 x 24 inch)
Ferromagnetic engraving table	Allows to mount thin materials such as paper, films or foils with magnets to ensure an even and flat surface to achieve optimal results
Vacuum table	Vacuum effect for fixation of thin or wavy materials
Acrylic cutting grid table (white)	Reflection free cutting of parts smaller than 100 mm (4 inch)
Slat cutting table	Reflection-free cutting of thicker materials and parts bigger than 100 mm (4 inch); removable aluminium and acrylic slats, x-axis ruler can be removed and mounted again without re-adjustment
Honeycomb cutting table	Good compromise between the Grid and Slat table configuration. The thin support structures reduce flashback compared to a grid table and combined with the high density of the honeycomb structure still provides good support for less rigid material such as thin plastic, card & paper or membrane boards; available with 12,7 mm (0.5 inch) or 6,4 mm (0.25 inch) nominal comb size
Rotary attachment	Cone, roll or combined version, tilt able Max. workpiece length cones: 730 mm (33.8 inch) Max. workpiece length rolls: $\varnothing \geq 58$ mm (2.2 inch) = 889 mm (35.0 inch), $\varnothing \leq 58$ mm (2.2 inch) = 958 mm (37.7 inch) Max. workpiece diameter cones: 270 mm (10.6 inch), depending on lens Max. workpiece diameter rolls: 180 mm (7 inch), depending on lens
TroCare	Comprehensive package of technical services

Laser

Laser system CO ₂	Sealed-off laser, maintenance free, air cooled, wavelength 10.6 µm 60, 80, 100 and 120 W
------------------------------	---

Dimensions & weight

Width x Depth x Height 1428 x 952* x 1072,5 mm (56.2 x 38.5* x 42.2 inch)
* top lid closed, without mounted exhaust hose connections, gas-kit light

Weight Approx. 295 – 310 kg / 650 - 684 lbs (depending on laser power)

Safety & environment

Laser class CDRH laser class 2

Interlock Safety system with Individually checked Interlocks, optional with Dual-coded interlocks

Loading lid Ergonomic down/up-lift front lid

Ambient conditions Mandatory ambient temperature +15° to +25° C or 59° to 77° F
Humidity 40% to max. 70%, not condensing
Dust free environment (2nd degree according to IEC 60947-1)

Certificates CE compliant, FDA listed

Exhaust

Minimum volume required (without piping/tubing) 400 m³/h at 4.200 Pa
Two connections

Required Atmos Duo Plus (or equivalent systems, all table concepts)
Vent Set 400 (or equivalent systems; all table concepts except vacuum table/strong vacuum effect)
Vent Set 500 (or equivalent systems, all table concepts incl. vacuum table/strong vacuum effect)

Cooling

Air cooling Active air flow cooling with fan

Liquid cooling Optional available for CO₂ laser sources 60 – 120 watts with external liquid cooler

Electrical

Voltage & power consumption 1 ~ AC 110-230V 50/60Hz, approx. 1200 W to 2100 W
(depending on laser power)

Subject to change without notice. Errors and omissions reserved.

Model identification Speedy 400C-8086

October 2023